

Z-1Mini

Intelligent 4K Full-Color Night Vision Micro Pod



Characteristics

- 4K resolution and AI-ISP full-color night vision imaging engine empowerment.
- Features AI multi-object detection and tracking, which can constantly track one of the persons and vehicles intelligently identified in the image.
- Micro 3-axis nonorthogonal mechanical stabilized structure reducing the weight down to 69g.
- Supports network, UART and S.BUS control and compatible with both private protocol and MAVLink protocol. Supports image transmission though network and HDMI.
- Thanks to the Dual-IMU complementary algorithms with IMU temperature control and carrier AHRS fusion, the gimbal provides a stabilization accuracy at $\pm 0.01^\circ$.
- Can be mounted onto multiple carriers, whether downward or upward.
- With the Dragonfly software, user can watch the image and control the pod without protocol ducking.
- With the customized QGC software, all the functions of the pod can be achieved in conjunction with an open source autopilot.
- Screen supports overlaying OSD information such as latitude, longitude and altitude. Image supports shooting point coordinate EXIF save.
- 10~26.4 VDC wide voltage input.

Specifications

| General | |
|--------------------------------------|---|
| Product Name | Z-1Mini |
| Dimensions | 50.2 x 48.4 x 67.4mm |
| Weight | 69g |
| Operating Voltage | 10 ~ 26.4VDC |
| Power | 4.5W (AVG) / 18W (Stall) |
| Mounting | Downward / Upward |
| Gimbal | |
| Gimbal Type | 3-axis Nonorthogonal Mechanical Stabilization |
| Angular Accuracy | ±0.01° |
| Controllable Range | Pitch: ±120°, Roll: ±60°, Yaw: ±160° |
| Max Controllable Speed | ±200°/s |
| Fixed Camera | |
| Image Sensor | 1/2.8-inch CMOS, Effective Pixels: 8.29M |
| Lens | Actual Focal Length: 6.0mm (Equivalent focal length: 34.4mm) |
| | Aperture: f/1.0 |
| | HFOV: 54.7° |
| | VFOV: 30.2° |
| DFOV: 63.2° | |
| Resolution | 3840(H) x 2160(V) |
| Pixel Size | 1.45µm(H) x 1.45µm(V) |
| Equivalent Digital Zoom Rate | 8x |
| Object Detection Distance | EN62676-4:2015 Person ^[1] : 175m; Light vehicle ^[2] : 230m; Large vehicle ^[3] : 491m |
| | Johnson Criteria Person: 2069m; Light vehicle: 6345m; Large vehicle: 13517m |
| Object Identification Distance | EN62676-4:2015 Person: 35m; Light vehicle: 46m; Large vehicle: 98m |
| | Johnson Criteria Person: 517m; Light vehicle: 1586m; Large vehicle: 3379m |
| Object Verification Distance | EN62676-4:2015 Person: 18m; Light vehicle: 23m; Large vehicle: 49m |
| | Johnson Criteria Person: 259m; Light vehicle: 793m; Large vehicle: 1690m |
| AI Multi-object Detection & Tracking | |
| Object Size | 16x16 ~ 128x128 px |
| Object Identification Delay | < 40ms |
| Tracking Speed | ±32 px / field |
| Tracking Deviation Refresh Rate | 30Hz |
| Tracking Deviation Output Delay | ≤5ms |

[1] Reference dimension of person: 1.8x0.5m. Critical dimension under Johnson criteria is 0.75m

[2] Reference dimension of light vehicle: 4.2x1.8m. Critical dimension under Johnson criteria is 2.3m

[3] Reference dimension of large vehicle: 6.0x4.0m. Critical dimension under Johnson criteria is 4.9m

| Image & Video | |
|--------------------------|---|
| Image Format | JPEG |
| Maximum Image Resolution | 3840 x 2160 |
| EXIF | Shooting point coordinate |
| Video Format | MP4 |
| Maximum Video Resolution | Stream: 1920 x 1080 @30fps Recording: 3840 x 2160 @30fps |
| Stream Encode Format | H.264 , H.265 |
| Stream Network Protocol | RTSP |
| Storage | |
| Supported SD Cards | Supports a Speed Class 10 MicroSD card with a capacity of up to 256GB |
| Environment | |
| Operating Temperature | -20°C ~ 50°C |
| Storage Temperature | -40°C ~ 60°C |
| Operating Humidity | ≤85%RH (Non-condensing) |