## Z-1Pro

## **Intelligent Black Light Full-Color Night Vision Micro Pod**



## **Characteristics**

- 1/1.8-inch star-light CMOS and AI-ISP full-color night vision imaging technology empowerment.
- Features AI multi-object detection and tracking, which can constantly track one
  of the persons and vehicles intelligently identified in the image.
- Micro 3-axis nonorthogonal mechanical stabilized structure reducing the weight down to 100g.
- Supports network, UART and S.BUS control and compatible with both private protocol and MAVLink protocol. Support image transmission though network and HDMI.
- Thanks to the Dual-IMU complementary algorithms with IMU temperature control and carrier AHRS fusion, the gimbal provides a stabilization accuracy at ±0.01°.
- Can be mounted onto multiple carriers, whether downward or upward.
- With the Dragonfly software, user can watch the image and control the pod without protocol ducking.
- With the customized QGC software, all the functions of the pod can be achieved in conjunction with an open source autopilot.
- Screen supports overlaying OSD information such as latitude, longitude and altitude. Image supports shooting point coordinate EXIF save.
- 10~26.4 VDC wide voltage input.

## **Specifications**

General			
Product Name	Z-1 <sub>Pro</sub>		
Dimensions	59.2 x 48.4 x 80.2mm		
Weight	100g		
Operating Voltage	10 ~ 26.4VDC		
Power	6W (AVG) / 20W (Stall)		
Mounting	Downward / Upward		
Gimbal			
Gimbal Type	3-axis Nonorthogonal Mechanical Stabilization		
Angular Accuracy	±0.01°		
Controllable Range	Pitch: -135° $\sim$ +100°, Roll: $\pm$ 50°, Yaw: $\pm$ 150°		
Max Controllable Speed	±200°/s		
Fixed Camera			
Image Sensor	1/1.8-inch CMOS, Effective Pixels: 4.08M		
Lens	Actual Focal Length: 8.5mm (Equivalent focal length: 34.8mm)  Aperture: f/1.0  HFOV: 57.1°  VFOV: 30.4°  DFOV: 66.3°		
Resolution	2688(H) x 1520(V)		
Pixel Size	2.9μm(H) x 1520(V)		
Equivalent Digital Zoom Rate	6x		
Object Detection Distance	EN62676-4:2015 Johnson Criteria	Person <sup>[1]</sup> : 122m; Light vehicle <sup>[2]</sup> : 161m; Large vehicle <sup>[3]</sup> : 343m Person: 1466m; Light vehicle: 4494m; Large vehicle: 9575m	
Object Identification Distance	EN62676-4:2015	Person: 25m; Light vehicle: 32m; Large vehicle: 69m	
•	Johnson Criteria	Person: 366m; Light vehicle: 1124m; Large vehicle: 2394m	
Object Verification Distance	EN62676-4:2015	Person: 12m; Light vehicle: 16m; Large vehicle: 34m	
	Johnson Criteria	Person: 183m; Light vehicle: 562m; Large vehicle: 1197m	
AI Multi-object Detection &	•		
Object Size	16x16 ~ 128x128 px		
Object Identification Delay	< 40ms		
Tracking Speed	±32 px / field		
Tracking Deviation Refresh Rate	30Hz		
Tracking Deviation Output Delay	≤5ms		

- [1] Reference dimension of person: 1.8x0.5m. Critical dimension under Johnson criteria is 0.75m
- [2] Reference dimension of light vehicle: 4.2x1.8m. Critical dimension under Johnson criteria is 2.3m
- [3] Reference dimension of large vehicle: 6.0x4.0m. Critical dimension under Johnson criteria is 4.9m

Image & Video		
Image Format	JPEG	
Maximum Image Resolution	2688 x 1520	
EXIF	Shooting point coordinate	
Video Format	MP4	
Maximum Video Resolution	Stream: 1920 x 1080 @30fps	
Maximum video Resolution	Recording: 2688 x 1520 @30fps	
Stream Encode Format	H.264 , H.265	
Stream Network Protocol	RTSP	
Storage		
Supported SD Cards	Supports a Speed Class 10 MicroSD card with a capacity of up to 256GB	
Environment		
Operating Temperature	-20℃ ~ 50℃	
Storage Temperature	-40°C ~ 60°C	
Operating Humidity	≤85%RH (Non-condensing)	